

FEATURES & BENEFITS

 reliable fastening of cable bundle to enclosure, e.g. by a screw

 vibration-resistant fastening

 for indoor use

LOGISTIC DATA

Quantity in package [pcs] 100

MECHANICAL DATA

Material polyamide 6.6

Halogen-free yes

Operating temperature [°C] -40 ÷ +85

Minimum installation temperature [°C] 0

CERTIFICATES & STANDARDS

Flammability class UL 94 V2

Standards EN IEC 62275:2019

NOTE!

UL certificate - for up-to-date information, visit www.ergom.com



Type	Index Ergom	Colour	Tensile strength, min. [daN]	Max. bundle dia. [mm]	Fastening screw	Tool type	L	W
TKO 9/3 (100 PCS)	E01TK-01040100101	natural (bright)	8	19	M3	MK III A, MK III PR	110	2,5
TKO 14/3,6 (100 PCS)	E01TK-01040100201	natural (bright)	18	32	M4	MK III A, MK III B, MK III C, MK III PR	150	3,6
TKO 16/5 (100 PCS)	E01TK-01040100281	natural (bright)	22	36,8	M5		160	4,8
TKO 20/5 (100 PCS)	E01TK-01040100301	natural (bright)	22	50	M5	MK III A, MK III B, MK III C, MK III PR	200	4,8
TKO 30/5 (100 PCS)	E01TK-01040100501	natural (bright)	22	82,8	M5	MK III A, MK III B, MK III C, MK III PR	300	4,8
TKO 40/5 (100 PCS)	E01TK-01040100601	natural (bright)	22	102	M5	MK III A, MK III B, MK III C, MK III PR	370	4,8
TKO 20/8 (100 PCS)	E01TK-01040100701	natural (bright)	54	44	M6	MK III B, MK III C	200	7,6
TKO 40/8 (100 PCS)	E01TK-01040100801	natural (bright)	54	109,2	M6	MK III B, MK III C	400	7,6
TKO 20/5 BK (100 PCS)	E01TK-01040100401	black	22	49,8	M5	MK III A, MK III B, MK III C, MK III PR	200	4,8
TKO 40/8 BK (100 PCS)	E01TK-01040100901	black	54	109,2	M6	MK III B, MK III C	400	7,6

