

FEATURES & BENEFITS



cable ties with built-in steel insert; perfect quality of cable bundle fastening



for indoor use

LOGISTIC DATA

Quantity in package [pcs] 100

MECHANICAL DATA

Material polyamide 6.6; stainless steel

Halogen-free yes

Colour natural (bright)

Operating temperature [°C] -40 ÷ +85

Minimum installation temperature [°C] 0

CERTIFICATES & STANDARDS

Flammability class UL 94 V2

Standards EN IEC 62275:2019



CE

Type	Index Ergom	Tensile strength, min. [daN]	Max. bundle dia. [mm]	Tool type	L	W
TY 9/3 (100 PCS)	E01TK-01120100101	8	16	MK III A, MK III PR	92	2,4
TY 20/3 (100 PCS)	E01TK-01120100201	8	50	MK III A, MK III PR	200	2,4
TY 14/3,6 (100 PCS)	E01TK-01120100301	18	29	MK III A, MK III B, MK III C, MK III PR	140	3,6
TY 20/3,6 (100 PCS)	E01TK-01120100401	18	50	MK III A, MK III B, MK III C, MK III PR	208	3,6
TY 30/3,6 (100 PCS)	E01TK-01120100501	18	76	MK III A, MK III B, MK III C, MK III PR	281	3,6
TY 40/3,6 (100 PCS)	E01TK-01120100601	18	103	MK III A, MK III B, MK III C, MK III PR	368	3,6
TY 20/5 (100 PCS)	E01TK-01120100701	22	45	MK III A, MK III B, MK III C, MK III PR	186	4,8
TY 30/5 (100 PCS)	E01TK-01120100801	22	78	MK III A, MK III B, MK III C, MK III PR	293	4,8
TY 40/5 (100 PCS)	E01TK-01120100901	22	102	MK III A, MK III B, MK III C, MK III PR	360	4,8
TY 20/8 (100 PCS)	E01TK-01120101001	54	50	MK III B, MK III C	223	7,6
TY 30/8 (100 PCS)	E01TK-01120101101	54	90	MK III B, MK III C	338	7,6
TY 70/8 (100 PCS)	E01TK-01120101201	54	229	MK III B, MK III C	762	7,0