

Angle ring terminals, K450 type

FEATURES & BENEFITS

- ✓ ring terminal Cu, as per DIN, palm of cable terminal is bent at 45 degrees relative to the tubular part crimped on the wire
- ✓ description of cable cross-section and cable lug size on palm surface
- ✓ soldered seam of the tubular part

LOGISTIC DATA

Quantity in package [pcs] 100

MECHANICAL DATA

Material Cu
Surface tin-plated


CERTIFICATES & STANDARDS

Design DIN 46234 - before palm bending

NOTE!

Use tools as for KO terminals.

Bending can be made at different angle.



Type	Index Ergom	Cross-section [mm²]	Screw hole	d	D	s	a	W	Weight [kg]
K450 1/2,5 (100 PCS)	E09KO-01040100700	0,75+1,0	M2,5	1,6	3,2	0,8	5	6	0,06
K450 1/3 (100 PCS)	E09KO-01040100800		M3						
K450 1/3,5 (100 PCS)	E09KO-01040100900		M3,5						
K450 1/4 (100 PCS)	E09KO-01040101000		M4						
K450 1/5 (100 PCS)	E09KO-01040101100		M5					10	0,08
K450 1/6 (100 PCS)	E09KO-01040101200		M6						0,07
K450 1/8 (100 PCS)	E09KO-01040101300		M8					14	0,12
K450 1/10 (100 PCS)	E09KO-01040101400		M10						0,1
K450 2,5/3 (100 PCS)	E09KO-01040101500	1,5+2,5	M3	2,3	3,9	0,8	5	6	0,06
K450 2,5/3,5 (100 PCS)	E09KO-01040101600		M3,5					8	0,08
K450 2,5/4 (100 PCS)	E09KO-01040101700		M4					10	0,09
K450 2,5/5 (100 PCS)	E09KO-01040101800		M5					11	0,11
K450 2,5/6 (100 PCS)	E09KO-01040101900		M6					14	0,13
K450 2,5/8 (100 PCS)	E09KO-01040102000		M8					18	0,17
K450 2,5/10 (100 PCS)	E09KO-01040102100		M10						
K450 6/3,5 (100 PCS)	E09KO-01040102400	4,0+6,0	M3,5	3,6	5,6	1,0	6	8	0,14
K450 6/4 (100 PCS)	E09KO-01040102500		M4					10	0,16
K450 6/5 (100 PCS)	E09KO-01040102600		M5					11	0,17
K450 6/6 (100 PCS)	E09KO-01040102700		M6					14	0,21
K450 6/8 (100 PCS)	E09KO-01040102800		M8					18	0,27
K450 6/10 (100 PCS)	E09KO-01040102900		M10						
K450 10/4 (100 PCS)	E09KO-01040103100	10	M4	4,5	6,7	1,1	8	10	0,24
K450 10/5 (100 PCS)	E09KO-01040103200		M5					11	0,23
K450 10/6 (100 PCS)	E09KO-01040103300		M6					14	0,28
K450 10/8 (100 PCS)	E09KO-01040103400		M8					18	0,34
K450 10/10 (100 PCS)	E09KO-01040103500		M10						

Type	Index Ergom	Cross-section [mm²]	Screw hole	d	D	s	a	W	Weight [kg]
K45O 16/5 (100 PCS)	E09KO-01040103700	16	M5	5,8	8,2	1,2	10	11	0,38
K45O 16/6 (100 PCS)	E09KO-01040103800		M6						0,36
K45O 16/8 (100 PCS)	E09KO-01040103900		M8					14	0,42
K45O 16/10 (100 PCS)	E09KO-01040104000		M10					18	0,5
K45O 25/5 (100 PCS)	E09KO-01040104200	25	M5	7,5	10,5	1,5	11	12	0,72
K45O 25/6 (100 PCS)	E09KO-01040104300		M6						0,7
K45O 25/8 (100 PCS)	E09KO-01040104400		M8					16	0,77
K45O 25/10 (100 PCS)	E09KO-01040104500		M10					18	0,8
K45O 25/12 (100 PCS)	E09KO-01040104650		M12					22	0,98
K45O 35/6 (100 PCS)	E09KO-01040104800	35	M6	9,0	12,2	1,6	12	15	1
K45O 35/8 (100 PCS)	E09KO-01040104900		M8					16	0,97
K45O 35/10 (100 PCS)	E09KO-01040105000		M10					18	0,98
K45O 35/12 (100 PCS)	E09KO-01040105150		M12					22	1,2
K45O 50/6 (100 PCS)	E09KO-01040105400	50	M6	11,0	14,6	1,8	16	18	1,65
K45O 50/8 (100 PCS)	E09KO-01040105500		M8						1,75
K45O 50/10 (100 PCS)	E09KO-01040105600		M10						1,63
K45O 50/12 (100 PCS)	E09KO-01040105750		M12					22	1,85