

Angle ring terminals, K900 type

FEATURES & BENEFITS

- ✓ ring terminal Cu, as per DIN, palm of cable terminal is bent at 90 degrees relative to the tubular part crimped on the wire
- ✓ description of cable cross-section and cable lug size on palm surface
- ✓ soldered seam of the tubular part

LOGISTIC DATA

Quantity in package [pcs] 100

MECHANICAL DATA

Material Cu
Surface tin-plated


CERTIFICATES & STANDARDS

Design DIN 46234 - before palm bending

NOTE!

Use tools as for KO terminals.

Bending can be made at different angle.



Type	Index Ergom	Cross-section [mm²]	Screw hole	d	D	s	a	W	Weight [kg]
K900 1/2,5 (100 PCS)	E09KO-01060100700	0,75+1,0	M2,5	1,6	3,2	0,8	5	6	0,06
K900 1/3 (100 PCS)	E09KO-01060100800		M3						
K900 1/3,5 (100 PCS)	E09KO-01060100900		M3,5						
K900 1/4 (100 PCS)	E09KO-01060101000		M4					8	0,07
K900 1/5 (100 PCS)	E09KO-01060101100		M5					10	0,08
K900 1/6 (100 PCS)	E09KO-01060101200		M6					14	0,07
K900 1/8 (100 PCS)	E09KO-01060101300		M8						0,12
K900 1/10 (100 PCS)	E09KO-01060101400	1,5+2,5	M10	2,3	3,9	0,8	5	14	0,1
K900 2,5/3 (100 PCS)	E09KO-01060101500		M3					6	0,06
K900 2,5/3,5 (100 PCS)	E09KO-01060101600		M3,5						
K900 2,5/4 (100 PCS)	E09KO-01060101700		M4					8	0,08
K900 2,5/5 (100 PCS)	E09KO-01060101800		M5					10	0,09
K900 2,5/6 (100 PCS)	E09KO-01060101900		M6					11	0,11
K900 2,5/8 (100 PCS)	E09KO-01060102000		M8					14	0,13
K900 2,5/10 (100 PCS)	E09KO-01060102100	4,0+6,0	M10					18	0,17
K900 6/3,5 (100 PCS)	E09KO-01060102400		M3,5	3,6	5,6	1,0	6	8	0,14
K900 6/4 (100 PCS)	E09KO-01060102500		M4					10	0,16
K900 6/5 (100 PCS)	E09KO-01060102600		M5						
K900 6/6 (100 PCS)	E09KO-01060102700		M6					11	0,17
K900 6/8 (100 PCS)	E09KO-01060102800		M8					14	0,21
K900 6/10 (100 PCS)	E09KO-01060102900		M10					18	0,27
K900 10/4 (100 PCS)	E09KO-01060103100	10	M4	4,5	6,7	1,1	8	10	0,24
K900 10/5 (100 PCS)	E09KO-01060103200		M5					11	0,23
K900 10/6 (100 PCS)	E09KO-01060103300		M6						
K900 10/8 (100 PCS)	E09KO-01060103400		M8					14	0,28
K900 10/10 (100 PCS)	E09KO-01060103500		M10					18	0,34

Type	Index Ergom	Cross-section [mm ²]	Screw hole	d	D	s	a	W	Weight [kg]
K90O 16/5 (100 PCS)	E09KO-01060103700	16	M5	5,8	8,2	1,2	10	11	0,38
K90O 16/6 (100 PCS)	E09KO-01060103800		M6						0,36
K90O 16/8 (100 PCS)	E09KO-01060103900		M8					14	0,42
K90O 16/10 (100 PCS)	E09KO-01060104000		M10					18	0,5
K90O 25/5 (100 PCS)	E09KO-01060104200	25	M5	7,5	10,5	1,5	11	12	0,72
K90O 25/6 (100 PCS)	E09KO-01060104300		M6						0,7
K90O 25/8 (100 PCS)	E09KO-01060104400		M8					16	0,77
K90O 25/10 (100 PCS)	E09KO-01060104500		M10					18	0,8
K90O 35/6 (100 PCS)	E09KO-01060104800	35	M6	9,0	12,2	1,6	12	15	1
K90O 35/8 (100 PCS)	E09KO-01060104900		M8					16	0,97
K90O 35/10 (100 PCS)	E09KO-01060105000		M10					18	0,98
K90O 50/6 (100 PCS)	E09KO-01060105400	50	M6	11,0	14,6	1,8	16	18	1,65
K90O 50/8 (100 PCS)	E09KO-01060105500		M8						1,75
K90O 50/10 (100 PCS)	E09KO-01060105600		M10						1,63