

Tubular ring cable lugs, KORI type

FEATURES & BENEFITS

- ✓ ring cable lug Cu, standard, with galvanic tin plating and insulating sleeve
- ✓ description of cable cross-section and cable lug size on palm surface
- ✓ insulating sleeve: enhances resistance to vibrations, mitigates short-circuit risk, facilitates cable installation
- ✓ sleeve colours facilitate cross-section identification

LOGISTIC DATA

Quantity in package [pcs] 100

MECHANICAL DATA

Insulation polyamide 6.6

Material Cu

Surface tin-plated

Operating temperature [°C] -30 ÷ +95


CERTIFICATES & STANDARDS

Design standard

NOTE!

Sector shaped conductors (sm) must be rounded with special dies.

Larger sizes up to 120 mm² on request.



Type	Index Ergom	Cross-section, mm²	d	D	a	E	L	W	Insulation colour	Screw hole	Weight [kg]
KORI 10/5 (100 PCS)	E11KM-01100000100	10	4,5	7,5	10	21,0	17,5	12,0	red	M5	0,55
KORI 10/6 (100 PCS)	E11KM-01100000200					21,5		12,0		M6	0,54
KORI 10/8 (100 PCS)	E11KM-01100000300					23,5		15,0		M8	0,62
KORI 10/10 (100 PCS)	E11KM-01100000400					25,5		17,0		M10	0,67
KORI 10/12 (100 PCS)	E11KM-01100000500					26,5		19,0		M12	0,66
KORI 16/5 (100 PCS)	E11KM-01100001100	16	5,5	9,6	13	25,0	22,0	12,0	blue	M5	0,94
KORI 16/6 (100 PCS)	E11KM-01100001200					25,5		12,0		M6	0,93
KORI 16/8 (100 PCS)	E11KM-01100001300					27,5		15,0		M8	1
KORI 16/10 (100 PCS)	E11KM-01100001400					29,5		17,0		M10	1,03
KORI 16/12 (100 PCS)	E11KM-01100001500					30,5		19,0		M12	1,13
KORI 25/5 (100 PCS)	E11KM-01100002100	25	7,0	12,0	15	28,0	25,0	14,0	yellow	M5	1,22
KORI 25/6 (100 PCS)	E11KM-01100002200					28,5		14,0		M6	1,26
KORI 25/8 (100 PCS)	E11KM-01100002300					30,5		16,0		M8	1,29
KORI 25/10 (100 PCS)	E11KM-01100002400					32,5		18,0		M10	1,34
KORI 25/12 (100 PCS)	E11KM-01100002500					33,5		19,0		M12	1,34
KORI 25/14 (100 PCS)	E11KM-01100002600	35	8,5	13,0	17	35,5	28,0	21,0	red	M14	1,49
KORI 35/6 (100 PCS)	E11KM-01100003100					31,5		18,0		M6	1,65
KORI 35/8 (100 PCS)	E11KM-01100003200					33,5		18,0		M8	1,85
KORI 35/10 (100 PCS)	E11KM-01100003300					35,5		20,0		M10	1,99
KORI 35/12 (100 PCS)	E11KM-01100003400					36,5		20,0		M12	2,15
KORI 35/14 (100 PCS)	E11KM-01100003500	35	8,5	13,0	17	38,5	28,0	21,0	red	M14	2,1
KORI 35/16 (100 PCS)	E11KM-01100003600					39,5		26,0		M16	2,25