

“Butt splice” compression cable connectors, ZMD type

FEATURES & BENEFITS



connector made of DIN Cu-tube, without galvanic tin plating,



central stamping guarantees correct length of conductor insertion



not mechanically loaded

MECHANICAL DATA


Material	Cu
Surface	uncoated

CERTIFICATES & STANDARDS

Design	DIN 46267 part 1
--------	------------------

NOTE!

Sector-shaped conductors (sm) must be rounded with special dies.



Type	Index Ergom	Cross-section, rm/ sm [mm ²]	d	D	L	Socket code no.	Lz/s	Lz/w	Quantity in package [pcs]
ZMD 10 (50 PCS)	E11KM-02060200100	10	4,5	6,0	30	6	1 - 1	2 - 2	50
ZMD 16 (50 PCS)	E11KM-02060200200	16	5,5	8,5	50	8	1 - 1	2 - 2	50
ZMD 25 (50 PCS)	E11KM-02060200300	25	7,0	10,0	50	10	1 - 1	2 - 2	50
ZMD 35 (50 PCS)	E11KM-02060200400	35	8,2	12,5	50	12	1 - 1	2 - 2	50
ZMD 50 (10 PCS)	E11KM-02060200500	50	10,0	14,5	56	14	1 - 1	3 - 3	10
ZMD 70 (10 PCS)	E11KM-02060200600	70	11,5	16,5	56	16	1 - 1	3 - 3	10
ZMD 95 (10 PCS)	E11KM-02060200700	95	13,5	19,0	70	18	2 - 2	4 - 4	10
ZMD 120 (10 PCS)	E11KM-02060200800	120	15,5	21,0	70	20	2 - 2	4 - 4	10
ZMD 150 (10 PCS)	E11KM-02060200900	150	17,0	23,5	80	22	2 - 2	4 - 4	10
ZMD 185 (10 PCS)	E11KM-02060201000	185	19,0	25,5	85	25	2 - 2	5 - 5	10
ZMD 240 (10 PCS)	E11KM-02060201100	240	21,5	29,0	90	28	2 - 2	5 - 5	10
ZMD 300	E11KM-02060201200	300	24,5	32,0	100	32	2 - 2	6 - 6	1
ZMD 400	E11KM-02060201300	400	27,5	38,5	150	38	3 - 3	-	1
ZMD 500	E11KM-02060201400	500	31,0	42,0	160	42	3 - 3	-	1
ZMD 625	E11KM-02060201500	625	34,5	44,0	160	44	3 - 3	-	1

Lz/s - Number of crimping - wide, Lz/w - Number of crimping - narrow