

Hydraulic crimping tool, WHPH 4

FEATURES & BENEFITS

- ☒ crimping dies for HP system
- ☒ side crimping head "inlet"
- ☒ non-opened crimping head
- ☒ pressure force: 130 kN

LOGISTIC DATA

Type	WHPH 4
Index Ergom	E06PZ-05110005000
Weight [kg]	6

Side crimping head „inlet“ facilitates crimping terminals in inaccessible locations and limited space. Replaceable crimping dies. Movable handle lock, in 'closed' position.

MECHANICAL DATA

Die type	HP
Head "entry" depth [mm]	32
Crimping force [kN]	130
Working pressure [MPa]	70
Piston stroke [mm]	42
Length [mm]	560
Crimping range	10 ÷ 400

CRIMPING

Terminal group	Cable cross-section [mm²]	Crimping shape
Al DIN	10-240	hexagon
Al-c	16-240	hexagon
Al-g	16-240	hexagon
Cu DIN	16-300	hexagon
Cu EKO - KREo, LE	10-95	hexagon
H...ERHN, HI...ERHL, HIG	10-185	trapezoid
HI 2x	4-16	trapezoid
KO, KW, KI, KOR, KL	10-150	indent
KOI, KWI, KII, KLI	10-120	oval
Standard Cu	16-400	hexagon
se	35-300	round forming
sm	10-300	round forming

SET CONTAINS

	Quantity included [pcs.]
WHPH 4	1
Plastic case	1
Instruction manual	1

