

Battery-powered professional hydraulic crimping tool, HKP 22 D MEL

FEATURES & BENEFITS



professional crimping tool with replaceable dies for system 22



rotary and opened working head



compact design facilitates crimping in limited spaces

LOGISTIC DATA

Type	HKP 22 D MEL
Index Ergom	E06PZ-05120011001
Weight [kg]	3,25

MECHANICAL DATA

Drive	Battery, Li-Ion 18 V 2.0 Ah
Die type	KP22
Rotate head angle [deg.]	180
Crimping force [kN]	62
Crimping time [s]	5+6
Working pressure [MPa]	55
Piston stroke [mm]	13
Length [mm]	395
Crimping range	6 ÷ 240

ELECTRICAL DATA

Battery charging time [min]	30
Number of crimps from one battery charge [pcs]	approx. 130 for 150 mm ² Cu standard (approximate value depends on the type of wire and tip, ambient temperature, etc.)
Battery voltage [V]	18
Battery capacity [mAh]	2000

NOTE!

KP22 dies must be ordered separately - we recommend ordering a complete set.

P Tools
professional



CE

CRIMPING

Terminal group	Cable cross-section [mm²]	Crimping shape
Al DIN	10-240	hexagon
Al-Cu	10-240	hexagon
Al-c	16-240	hexagon
Al-g	16-185	hexagon
Aluminum made according to DIN	16-300	Hexagon with teeth
CKOR, CKL	10-240	hexagon
Cu DIN	6-300	hexagon
Cu EKO - KREo, LE	10-240	hexagon
H...ERHN, HI...ERHL, HIG	10-240	trapezoid with fangs
HI 2x	6-16	trapezoid
KO, KW, KI, KOR, KL	10-95	indent
KOI, KWI, KII, KLI, KORI	10-120	oval
Standard Cu	10-400	hexagon
ZLA	16-95	crimping
ZLAF, ZLAFD	25-70	crimping
se	35-300	round forming
sm	10-300	round forming

SET CONTAINS	Quantity included [pcs.]	Comment
HKP 22 D MEL	1	-
EB-9 - 2Ah LI-ION	2	Battery
EH-9 LI-ION	1	Charger
Plastic case	1	-
Instruction manual	1	-