

Professional hydraulic crimping tool, HKP 22

P Tools
professional

FEATURES & BENEFITS

- ☒ professional crimping tool with in-built pressure source
- ☒ replaceable dies for system 22
- ☒ rotary and opened working head facilitates side and front "entry" to crimping head
- ☒ two-stage hydraulic system; number of lever movements to crimp elements - 5

LOGISTIC DATA

Type	HKP 22
Index Ergom	E06PZ-05160006101
Weight [kg]	3

MECHANICAL DATA

Drive	manual
Die type	KP22
Rotate head angle [deg.]	180
Crimping force [kN]	60
Length [mm]	415
Crimping range	6 ÷ 300

NOTE!

KP22 dies must be ordered separately - we recommend ordering a complete set.

CRIMPING

Terminal group	Cable cross-section [mm²]	Crimping shape
Al DIN	10-240	hexagon
Al-Cu	10-240	hexagon
Al-c	16-240	hexagon
Al-g	16-185	hexagon
CKOR, CKL	10-240	hexagon
Cu DIN	6-300	hexagon
Cu EKO - KREo, LE	10-240	hexagon
H...ERHN, HI...ERHL, HIG	10-185	trapezoid
HI 2x	6-16	trapezoid
KO, KW, KI, KOR, KL	10-95	indent
KOI, KWI, KII, KLI	10-120	oval
MJPB	16-35	hexagon
MJPT	16-120	hexagon
Standard Cu	10-400	hexagon
ZLA	16-95	crimping
ZLAF, ZLAFD	25-70	crimping
se	35-300	round forming
sm	10-300	round forming



CE

SET CONTAINS	Quantity included [pcs.]
HKP 22	1
Metal case	1
Instruction manual	1