

Professional hydraulic crimping tool, HKP 5 D

FEATURES & BENEFITS



professional crimping tool with replaceable dies for system 5



rotary and opened working head facilitates side and front "entry" to crimping head



compact design facilitates crimping in limited spaces

LOGISTIC DATA

Type	HKP 5 D
Index Ergom	E06PZ-05120011201
Weight [kg]	2,3

MECHANICAL DATA

Drive	manual
Die type	HK5-.../HKP5...
Rotate head angle [deg.]	180
Head "entry" depth [mm]	5
Crimping force [kN]	55
Working pressure [MPa]	55
Number of hydraulic system stages	1
Piston stroke [mm]	13
Length [mm]	380
Crimping range	6 ÷ 300

NOTE!

HK5 dies must be ordered separately - we recommend ordering a complete set.

CRIMPING

Terminal group	Cable cross-section [mm²]	Crimping shape
Al DIN	10-150	hexagon
Al-c	16-185	hexagon
Al-g	16-120	hexagon
Cu DIN	6-185	hexagon
Cu EKO - KREo, LE	10-120	hexagon
H...ERHN, HI...ERHL, HIG	50-95	trapezoid
HI 2x	16	trapezoid
KO, KW, KI, KOR, KL	10-35	indent
KOI, KWI, KII, KLI	70	oval
Standard Cu	16-240	hexagon
ZLA	16-120	crimping
se	50-240	round forming
sm	35-185	round forming

SET CONTAINS

Quantity included [pcs.]

HKP 5 D	1
Plastic case	1
Instruction manual	1

P Tools
professional



CE