

Three fold split manual punching dies N3W


FEATURES & BENEFITS

-  blanking dies with manual drive, e.g. open-ended spanner, equipped with draw bolt
-  Split slugs gets cut on three parts what makes possible fall free and can be disposed of easily
-  thrust bearing used facilitates hole cutting operations
-  draw mandrel included

NOTE!

Punching dies N3W larger than 40,5 are sold in sets with MOLYKOTE 1000 thread paste.

Autres dimensions disponibles sur demande.



Type	Index Ergom	Max. thickness of material (steel) [mm]	Spanner size	Internal thread of the punch K	Diameter of the hole to be cut A [mm]	Diameter of the through hole D [mm]
N3W 12,2/PG7/M12	E06WD-01020120050	1,5	17	1/4" UNF	12,2	9,55
N3W 15,4/PG9	E06WD-01020120100	2,0	17	3/8" UNF	15,4	9,55
N3W 16,2/M16	E06WD-01020120200	2,0	17	3/8" UNF	16,2	9,55
N3W 18,8/PG11	E06WD-01020120300	2,0	17	3/8" UNF	18,8	9,55
N3W 20,7/PG13/M20	E06WD-01020120400	2,0	17	3/8" UNF	20,7	9,55
N3W 22,8/PG16	E06WD-01020120500	2,0	17	3/8" UNF	22,8	9,55
N3W 25,5/M25	E06WD-01020120600	2,0	17	3/8" UNF	25,5	9,55
N3W 28,6/PG21	E06WD-01020120700	2,0	17	3/4" UNF	28,6	9,55
N3W 30,5/M30	E06WD-01020120800	2,0	17	3/4" UNF	30,5	9,55
N3W 32,5/M32	E06WD-01020120900	2,0	17	3/4" UNF	32,5	19,05
N3W 37,4/PG29	E06WD-01020121000	3,0	27	3/4" UNF	37,4	19,05
N3W 40,5/M40	E06WD-01020121100	3,0	27	3/4" UNF	40,5	19,05
N3W 47,5/PG36	E06WD-01020121200	3,0	27	3/4" UNF	47,5	19,05
N3W 50,5/M50	E06WD-01020121300	3,0	27	3/4" UNF	50,5	19,05
N3W 54,5/PG42	E06WD-01020121400	3,0	27	3/4" UNF	54,5	19,05
N3W 59,8/PG48	E06WD-01020121500	3,0	27	3/4" UNF	59,8	19,05
N3W 63,5/M63	E06WD-01020121600	3,0	27	3/4" UNF	63,5	19,05