

Grounding clamps, OU 18 - OU 165 type

FEATURES & BENEFITS



stainless-steel ties



clamp for direct mounting of up to 16 mm² cross-section cords



easy installation and guarantee of good electric and mechanical connection

LOGISTIC DATA

Quantity in package [pcs] 10

Earthing clamps are clenched on 18-165 mm pipes with 2 M6 screws. One of the screws works also as a clamp to copper wires of up to 16 mm² cross-section. Earthing clamps are used for equalizing potential in buildings, ensuring electric shock protection works properly.

MECHANICAL DATA

Bolt material galvanised steel

Clamp material galvanised steel

Tie material stainless steel

Recommended screwdriver tip type (flat) 7/1,2

Recommended screwdriver tip type (cross) PZ2

ELECTRICAL DATA

Number of clamps x cross-section [mm²] 1x2,5÷16

CERTIFICATES & STANDARDS

Standards EN 60999



CE

Type	Index Ergom	Max. diameter of earthing part [mm]	Recommended tightening torque [Nm]	Tie length [mm]	Tie width [mm]	Weight [g]
OU 18 (10 PCS)	R33RA-04030100113	18	2,6	136	14	260
OU 50 (10 PCS)	R33RA-04030100123	50	4,6	209	20	470
OU 120 (10 PCS)	R33RA-04030100133	120	4,6	425	20	580
OU 165 (10 PCS)	R33RA-04030100143	165	4,6	583	20	660