

FEATURES & BENEFITS

- ☒ terminal plates for mounting cables with SM, SE, RM, RE profile conductors
- ☒ cables with multi-wire conductors can be connected directly
- ☒ made of tin-plated copper; compatible with V (single or double) type terminals

LOGISTIC DATA

Quantity in package [pcs] 12

APPLICATION


Connecting V (single or double) clamps to busbars and flat terminals.

MECHANICAL DATA

Material galvanised copper

CERTIFICATES & STANDARDS

Standards EN 60947-7-1 (IEC 60947-7-1)



Type	Index Ergom	A	B	d	s	Clamp type	Cross-section [mm ²]	I _{max} (35°C) (DIN 43670) [A]
PV 1/8 (12 PCS)	R32RZ-03020100102	65	20	8,5	3	V 120 VD 120 (10-120)	60	237
PV 1/10 (12 PCS)	R32RZ-03020100202	65	20	10,5	3	V 120 VD 120 (10-120)	60	237
PV 2/8 (12 PCS)	R32RZ-03020200102	72	25	8,5	3	VN 300 (16-300) VD 300 (50-240)	75	287
PV 2/10 (12 PCS)	R32RZ-03020200202	72	25	10,5	3	VN 300 (16-300) VD 300 (50-240)	75	287
PV 2/12 (12 PCS)	R32RZ-03020200302	72	25	13	3	VN 300 (16-300) VD 300 (50-240)	75	287
PV 3/8 (12 PCS)	R32RZ-03020300102	72	25	8,5	4	VN 300 (16-300) VD 300 (50-240)	100	319
PV 3/10 (12 PCS)	R32RZ-03020300302	72	25	10,5	4	VN 300 (16-300) VD 300 (50-240)	100	319
PV 3/12 (12 PCS)	R32RZ-03020300402	72	25	13	4	VN 300 (16-300) VD 300 (50-240)	100	319